

POREBA

Патроны самоцентрирующие спиральные со стальным корпусом

Посадка	Кол. кулачков	Тип кулачков	Тип патрона	Размер патрона D [mm]										
				80	100	125	160	200	250	315	400	500	630	800
DIN 6350	3	[Иконка]	T105				X	X	X	X	X			
			T504	X	X	X	X	X	X	X	X	X	X	
	3	[Иконка]	T574	X	X	X	X	X	X	X	X	X	X	
			T505			X	X	X	X	X	X	X	X	
	3	[Иконка]	T575			X	X	X	X	X	X	X	X	
			T704		X	X	X	X	X	X	X	X	X	
	4	[Иконка]	T774			X	X	X	X	X	X	X	X	
			T705			X	X	X	X	X	X	X	X	
			T775			X	X	X	X	X	X	X	X	
	6	[Иконка]	T806						X	X	X	X	X	
T807								X	X	X	X	X		
				80	100	125	160	200	250	315	400	500	630	800
DIN 55026	3	[Иконка]	T514				5	5;6	5;6;8	6;8	6;8;11	8;11	11;15	
			T515				5	5;6	5;6;8	6;8	6;8;11	8;11	11;15	
	4	[Иконка]	T714				5	5;6	5;6;8	6;8	6;8;11	8;11	11;15	
			T715				5	5;6	5;6;8	6;8	6;8;11	8;11	11;15	
				80	100	125	160	200	250	315	400	500	630	800
DIN 55027	3	[Иконка]	T534			3;4	4;5	5;6	6;8	6;8;11	8;11	8;11	11;15	
			T535			3;4	4;5	5;6	6;8	6;8;11	8;11	8;11	11;15	
	4	[Иконка]	T734			3;4	4;5	5;6	6;8	6;8;11	8;11	8;11	11;15	
			T735			3;4	4;5	5;6	6;8	6;8;11	8;11	8;11	11;15	
				80	100	125	160	200	250	315	400	500	630	800
DIN 55029	3	[Иконка]	T544			3;4	3;4;5	4;5;6	6;8	6;8;11	8;11	8;11	11;15	
			T545			3;4	3;4;5	4;5;6	6;8	6;8;11	8;11	8;11	11;15	
	4	[Иконка]	T744			3;4	3;4;5	4;5;6	6;8	6;8;11	8;11	8;11	11;15	
			T745			3;4	3;4;5	4;5;6	6;8	6;8;11	8;11	8;11	11;15	
				80	100	125	160	200	250	315	400	500	630	800
Окончательная Регулировка	3	[Иконка]	T564			X	X	X	X	X	X	X	X	
			T565			X	X	X	X	X	X	X	X	
	6	[Иконка]	T864			X	X	X	X	X	X	X	X	
			T865			X	X	X	X	X	X	X	X	
										315	405	515	630	
Oil Chucks	3	[Иконка]	T597								X	X		

Сертификат ISO № 44100132840
TÜV NORD CERT GmbH.

Корпус - сталь C45,
28±2 HRC;

Спиральный диск - 42CrMo4 (40HM),
60±2 HRC;

Кулачки - 20MnCr5 (18HGT),
50±2 HRC;

Шестерня - 16MnCr5 (16HG),
48±2 HRC;

Смазка Gleitmo 805.

